





marlow industries, inc.®
Subsidiary of II-VI INCORPORATED



TECHNICAL DATA SHEET

Commercial Module for CATV & SLED Applications

CM29-1.9





T_A = 27°C - Vacuum



TYPICAL PERFORMANCE	
Environment : Vacuum	
T _A (C) :	27
V _{MAX} (VDC) :	3.5
Δ T _{MAX} (C) :	71
I _{MAX} (amps) :	1.9
Q _{MAX} (W) :	4.3
ACR (Ω) :	1.54

T_A = 85°C - Vacuum



TYPICAL PERFORMANCE	
Environment : Vacuum	
T _A (C) :	85
V _{MAX} (VDC) :	4.4
Δ T _{MAX} (C) :	92
I _{MAX} (amps) :	1.8
Q _{MAX} (W) :	5.2
ACR (Ω) :	-

ORDERING OPTIONS

Model Number	Description
CM29-1.9-01AC	Metallized Exterior
CM29-1.9-04AC	146°C Pretinned Exterior
CM29-1.9-05AC	138°C Pretinned Exterior

NOTES:

- RoHS 2002/95/EC Compliant.
- All dimensions are millimeters.
- All values are nominal values.
- Marlow reserves the right to make product changes without notice.
- Au flash exterior, suitable for soldering.
- AlO ceramics
- Minimum order quantity of 20 pieces.
- Maximum process temperature is 220°C.

CONTACT US:

For customer support or general questions please contact a local office below or consult our website for distributor information.

II-VI Singapore Pte., Ltd.
Blk. 5012, Techplace II
#04-07 & 05-07/12, Ang Mo Kio Ave. 5
Singapore 569876
(65) 6481 8215 (tel)
(65) 6481 8702 (fax)
info@ii-vi.com.sg
www.ii-vi.com.sg

Marlow Industries China, II-VI Technologies Beijing
A subsidiary of II-VI Incorporated
Rm 202, 1# Lize 2nd Middle Road
Wangjing, Chaoyang District
Beijing 100102 China
010-64398226 ext 105 (tel)
010-64399315 (fax)
info@iivibj.com